

ST917G IOT handheld Terminal

4.0-inch HD Screen · Android 10.0 system · 4G full Netcom barcode and UHF RFID reader long distance



Android



4G



WiFi



Bluetooth



UHF



1D barcode



2D barcode



SIM



NFC



Camera



GPS



Product parameters

Performance

Quad core	
CPU	Cortex-A53 Quad core 64 bit 2.0 GHz high performance processor
RAM+ROM	2GB+16GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 10.0

Data communication

WLAN	Dual-band 2.4GHz / 5GHz, Supporting IEEE 802 a/b/g/n/ac protocol
WWAN	2G: GSM (850/900/1800/1900MHz)
	3G: WCDMA (850/900/1900/2100MHz)
	4G: FDD:B1/B3/B4/B7/B8/B12/B20 TDD:B38/B39/B40/B41
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters
GNSS	Support Gps, Galileo, Glonass, Beidou

Physical parameter

Dimensions	201.8mm × 72mm × 140mm (Including the handle)
Weight	<750g (Depends on device function configuration)
Display	4.0 "color display with resolution 480 × 800
TP	support multi-touch
Battery capacity	Rechargeable polymer battery (7.6V 3750mah) removable
	Standby time >350 hours
	Working time > 12 hours
	Charging time <3H, using standard power adapter and data cable
Expansion Card slot	Nano SIM card × 2, TF card × 1
Communication interface	Type-C 2.0 USB × 1, supporting OTG function POGO Pin × 1
Audio	Speaker (mono), Microphone, Receiver
Keypad	38 soft and hard rubber buttons, left button x1, right button x1
Sensors	Gravity sensor, light sensor, distance sensor, vibration motor

Data collection

Barcode scanning (Optional)	
1D Scanning engine	Honeywell N5703
1D Symbologies	Code128,EAN-13,EAN-8,Code39,UPC-A,UPC-E, Codabar,Interleaved 2 of 5,China post 25,ISBN/ISSN, Code93,UCC/EAN-128,GS1 Databar,HIBC,etc.
2D Symbologies	PDF417,Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code,Micro QR Code,MaxiCode,Hanxin Code,etc.

Camera (Standard)

Rear camera	800W pixel HD camera Support auto focus, Flash, Anti-shake, Macro shooting
Front camera	500W pixel color camera

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 agreement
Distance	2cm-5cm

UHF (Optional)

Distance	0-13m
Reading speed	>200 tags per second (circular polarization)

Language/input method

Input	English, Pinyin, Five strokes, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese,Malaysian,etc.

User environment

Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH--95%RH(no condensation)
Drop specification	6 sides supports 1.2 meters drops on the marble within the operating temperature
Rolling test	0.5m rolling for 6 sides, can still work steadily
Sealing	IP66

Accessories

Standard	Adapter, Data cable, Protective film, Instruction manual
----------	---